



PHASE 1 BASEBALL FIELD
VIEWING BOX

SAW CUT
EXISTING
PAVING

MILL SURFACE PAVEMENT LAYER TO A DEPTH
OF 1.25 INCHES TO A WIDTH OF 18-INCHES TO
MATCH PHASE 2 SURFACE PAVEMENT

NEW WALK GRADE CANNOT EXCEED
5-PERCENT LONGITUDINALLY NOR
EXCEED A 2-PERCENT CROSS SLOPE.
CONTRACTOR SHALL CHECK ALL SPOT
GRADES AND CONTOUR ELEVATIONS
THROUGHOUT CONSTRUCTION TO
CONFIRM THAT THESE GRADE
THRESHOLDS WILL NOT BE EXCEEDED

CONTRACTOR SHALL CREATE A
SHALLOW SWALE TO CONVEY SURFACE
WATER FROM UP GRADIENT AREAS TO
FLOW ALONGSIDE THE NEW WALKWAY
AND TO DISCOURAGE RUNOFF FROM
FLOWING ONTO THE NEW WALKWAY
SURFACE

BASEBALL
FIELD

MEMORIAL TREES AND
BENCH TO BE PROTECTED
RIPRAP LINED DRAINAGE

CONCRETE PAD
WIDE 3-FOOT RIP RAP
INLET APPROX AT PIPE END
TO HAVE A D50 OF 4-INCHES WITH
DEPTH OF 8-INCHES. RIP RAP TO BE
REINFORCED BY MIRAFI 800X
TEXTILE FABRIC
MIS
IRTS

GATE CENTER
3' WIDE

WIDE 3-FOOT RIP RAP LINED
ANNEL BETWEEN PIPE ENDS. RIP
RAP TO HAVE A D50 OF 4-INCHES WITH
DEPTH OF 8-INCHES. RIP RAP TO BE
DERLINED BY MIRAFI 800X
TEXTILE FABRIC

8" PVC
INV.=53.88'

EXISTING
55.12

8" PVC
INV.=53.38'

EXISTING
55.19

8" PVC
INV.=53.40'

EXISTING
56.12

EXISTING 6-FOOT WIDE
PAVED WALK TO REGRADE
AND RESURFACE

EXISTING
57.34

REMOVE EXISTING BITUMING
PLACE NEW HOT MIX ASPHALT
TWO 1.25" LIFTS FOR A TOTAL
2.5-INCHES OF 9.2MM (NO. 20)
MATCH ORIGINAL EXISTING

GRANITE CURB,
SET FLUSH WITH
BRIDGE DECK
WOODEN
BRIDGE

EXISTING
57.96

EXISTING
58.88

EXISTING BRIDGE
DECK TO REMAIN

EXISTING
57.00

EXISTING
56.88

EXISTING
56.55

EXISTING
56.45

EXISTING
56.57

EXISTING
57.00

EXISTING
56.67

EXISTING
56.57

EXISTING
56.45

EXISTING
56.57

EXISTING
56.45

EXISTING
57.00

EXISTING
56.67

EXISTING
56.57

EXISTING
56.45

EXISTING
56.57

EXISTING
56.45